

PRODUCT INFORMATION

Typical Use	<p>Dulux Trade Hydrostrip 1003 is a water-based paint stripper suitable for the safe removal of decorative coatings from porous substrates, including wood, masonry and brick. It is also suitable for removing graffiti from bare, porous substrates.</p> <p>Before preparing any surface for painting, read the Health, Safety & Environmental information on page 2 about old lead-based paints.</p>
Codes according to the List of Wastes Regulations	<p>Product as supplied: Assigned as hazardous waste code 08 01 21* waste paint or varnish remover.</p> <p>Part-used containers, containing dried residues of the supplied product: Assigned as hazardous waste code 08 01 21* waste paint or varnish remover.</p> <p>Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.</p> <p>"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.</p> <p>These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.</p>
Pack Size	3.78 and 18.9 litre.
Colour Range	N/A
Composition (nominal)	<p>Pigment: N/A</p> <p>Binder: N/A</p> <p>Solvent: Benzyl alcohol, white spirit and water.</p>
Volume Solids	N/A
Application Method	<p>The product needs to be spray applied, using either airless or high volume low pressure spray. Atomisation of the product is undesirable. The recommended tip size is between 475 and 625 microns.</p> <p>Remove all filters from airless spray gun and pump. The product damages natural rubber and leather seals, so these should be replaced with neoprene seals and after use the pump should be cleaned out to ensure the seals last longer.</p> <p>Safety Precautions During Application:</p> <p>When applying, wear chemical splash goggles and rubber or neoprene gloves. If the product comes into direct contact with skin, wash thoroughly with water. See full Safety, Health and Environmental information below.</p> <p>Application Information:</p> <p>Most paint systems will lift when the stripper has been applied for 1 to 6 hours, but to obtain optimum results, it is recommended to allow the stripper to work overnight prior to removal. When removing multiple layers of paint, it may be necessary to re-apply the product.</p>
Practical Coverage	The coverage ranges between 1 and 2.2 m ² /litre. Variation depends on the thickness and type of coatings.
Cleaning Up	After use, remove as much stripper as possible from equipment before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

SYSTEM INFORMATION

Once the paint residue has been removed, wash the surface thoroughly with water. The stripped surface is now suitable for re-painting with an appropriate **Dulux Trade** paint system.

Do not store or collect the stripper in metal containers. Collect and dispose of the solid paint residue according to local authority regulations.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION
WATER-BASED PAINT STRIPPER

Harmful by inhalation and if swallowed.

Contains BENZYL ALCOHOL.

Use only in well ventilated areas.

Do not breathe vapour/spray.

Avoid contact with skin and eyes.

When using it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

Keep away from food, drink and animal feeding stuffs.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Before use refer to safety data sheet.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

See www.duluxtrade.co.uk

VOC Content High 25% - 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, The ICI Roundel and the distinctive livery are trademarks of AkzoNobel.

© AkzoNobel 2010 (05112010IT SDS1003)



HARMFUL

