

DULUX TRADE PRIMER SEALER

302

PRODUCT INFORMATION

Typical Use	<p>Dulux Trade Primer Sealer is a solvent-based sealer suitable for highly porous, dry, powdery and friable interior surfaces. It can also be used as a sealer over soft distemper. Aged, unpainted or textured plaster surfaces such as ceilings should be treated with Dulux Trade Primer Sealer prior to decorating.</p> <p>Before preparing any surface for painting, read the Health, Safety & Environmental information on page 2 about old lead-based paints.</p>
Codes according to the List of Wastes Regulations	<p>Product as supplied: Assigned as hazardous waste code 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.</p> <p>Part-used containers, containing dried residues of the supplied product: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11</p> <p>Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.</p> <p>"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.</p> <p>These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.</p>
Pack Size	1, 2.5 and 5 litre.
Colour Range	Off-white.
Composition (nominal)	<p>Pigment: Titanium Dioxide, Zinc Oxide and Inert Extenders.</p> <p>Binder: Oleoresin.</p> <p>Solvent: White Spirit.</p>
Volume Solids	49% (nominal).
Application Method	Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.
Drying Times	<p><i>Single coat at standard thickness:</i></p> <p>Touch Dry: 8-12 hours.</p> <p>Recoat: 16-24 hours.</p>
Practical Coverage	A guide to the practical coverage which can be achieved under normal conditions is up to 9m ² / litre.
Cleaning Up	After use, remove as much paint as possible from brushes before cleaning with white spirit. Do not use or store in extremes of temperature.

SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, efflorescence, dirt, grease, wax etc. Where necessary surfaces should be rubbed down using a suitable abrasive paper and then dusted off (refer to your COSHH Assessment).

SYSTEM INFORMATION

Stir thoroughly before use.

After suitable preparation, the normal recommendation is to apply one coat of **Dulux Trade** Primer Sealer, followed by the appropriate **Dulux Trade** finishing system.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION SOLVENT-BASED PAINT

Flammable.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Repeated exposure may cause skin dryness or cracking.

Contains cobalt carboxylate. May produce an allergic reaction.

Keep away from sources of ignition - no smoking.

Contains white spirit. Use only in well ventilated areas. Ensure maximum ventilation during application and drying.

When applying by brush or roller to large interior surface areas or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook. Do not empty into drains or watercourses.

Avoid release to the environment. Refer to special instructions/Safety data sheet.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

EU limit value for this product (cat A/h): 750g/l (2007) / 750g/l (2010)

This product contains max. 425g/l VOC

See www.duluxtrade.co.uk

VOC Content High 25% - 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, The ICI Roundel and the distinctive livery are trademarks of AkzoNobel.

© AkzoNobel 2010 (03112010IT SDS302)

