

DULUX TRADE CLEARCOAT

417

PRODUCT INFORMATION

Typical Use	<p>Dulux Trade Clearcoat is a water-based finish which enhances and protects the range of Dulux Trade special fashion effects. It is easy to apply and gives a high quality smooth matt finish, which provides superior durability and washability.</p> <p>Dulux Trade Clearcoat is quick-drying, of low odour and does not yellow on ageing. Before preparing any surface for painting, read the Health, Safety & Environmental information on page 2 about old lead-based paints.</p>
Codes according to the List of Wastes Regulations	<p>Product as supplied: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11.</p> <p>Part-used containers, containing dried residues of the supplied product: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11</p> <p>Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.</p> <p>"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.</p> <p>These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.</p>
Pack Size	2.5 and 5 litre.
Colour Range	N/A Clear only.
Film Properties	<p>Chemical Resistance: Not suitable.</p> <p>Heat Resistance: Not suitable for use on heated surfaces eg radiators.</p> <p>Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand repeated and frequent washing down. It is recommended for use where maximum durability in areas such as kitchens and bathrooms is required. Dulux Trade Clearcoat is not suitable for use on immersed surfaces or where there is very heavy and prolonged condensation.</p>
Composition (nominal)	<p>Pigment: N/A.</p> <p>Binder: Adhesion-promoted Acrylic Copolymer.</p> <p>Solvent: Water.</p>
Volume Solids	Satin 40% (nominal), Matt 24% (nominal).
Thinning	Do not thin this product.
Application Method	Brush, roller or spray.
Drying Times	<p><i>Single coat at standard thickness:</i></p> <p>Touch Dry: Dependent upon temperature and humidity.</p> <p>Recoat: 2-4 hours.</p>
Practical Coverage	A guide to the practical coverage which can be achieved under normal conditions is up to 20m ² / litre.
Spray Recommendations	<p>Conventional Spray: Satisfactory through most equipment.</p> <p>Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size 0.46mm (18 thou) and a spray tip angle 65°.</p>
Cleaning Up	After use, remove as much paint as possible from brushes before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

SURFACE PREPARATION

Surfaces must be clean and dry before sealing.

SYSTEM INFORMATION

This product must be stirred very thoroughly before use to incorporate any water layer that has formed on top of the paint in the can.

Apply 1 coat of **Dulux Trade** Clearcoat to clean, fully dry surfaces.

Dulux Trade Clearcoat will look milky when first applied but will dry to a clear finish.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION**WATER-BASED PAINT**

Ensure good ventilation during application and drying.

Do not breathe spray. When spraying inside, wearing a cartridge mask of Assigned Protection Factor 40 x OEL for particulates is recommended.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook. Do not empty into drains or watercourses.

Safety data sheet available for professional user on request.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

EU limit value for this product (cat A/i) : 140g/l (2007) / 140g/l (2010)

This product contains max. 70g/l VOC

See www.duluxtrade.co.uk

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, The ICI Roundel and the distinctive livery are trademarks of AkzoNobel.

© AkzoNobel 2010 (05112010IT SDS417)

