

DRY FALL EGGSHELL

Dulux Trade Dry Fall Eggshell is a high quality, durable, water-based mid-sheen finish for high production spray application to interior ceilings and walls. Overspray dries to a dust before reaching the floor on a drop of at least 10 feet and is easily cleaned up with a dry cloth or brush. It is ideal for use on large areas which must be painted with a minimum disruption of operations, such as offices, shops, factories, warehouses, hotels and institutional buildings. Also suitable for exterior overhead areas not subject to direct weathering such as covered car parks.

KEY BENEFITS

- Covers all Substrates
- Excellent Opacity & Adhesion
- Overspray dries to a dust*

PRODUCT INFORMATION

Typical Use

Suitable for use on any substrates where minimum disruption is desired.

Pack Size

10L.

Colour Range

White only.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer Emulsion.

Solvent: Water.

Volume Solids

43% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are clean, dry and free from all defective or poorly adhering material, dirt, grease and salts.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. The normal finishing process is to apply 1 coat of **Dulux Trade** Dry Fall Eggshell over a suitably prepared primed surface.

*At 25°C and 50% relative humidity, recoat time is 2 hours and overspray dries to a dust on falling a minimum of 10ft (3.3m). Low temperature and high humidity will increase drying time and dry fall-out distances.

APPLICATION METHOD

Airless spray only.

Do not use when the temperature is below 10°C.

DRY FALL EGGSHELL

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 6m² per litre.

Thinning

Not usually required, but if necessary thin with up to 1 part clean water to 10 parts paint.

Spray Recommendations

A test application is recommended to determine the tip size and pressure required to provide acceptable application and dry fall properties. A reduction in tip size will give improved dry fall. The use of new tips is recommended for best results.

Drying Times

Single coat at standard thickness:

Touch Dry: N/A

Recoat: 2 hours.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/a): 30g/l (2010). This product contains max. 10g/l VOC.
VOC content: Low (0.30-7.99%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 444) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp