

CELLAR PAINT

Dulux Trade Cellar Paint is formulated on a tough, durable solvent-based acrylic system unique to **AkzoNobel**. Its smooth consistency makes it easy to apply and discourages dirt retention. It can be applied to slightly damp (but not saturated) interior masonry surfaces.

KEY BENEFITS

- Tough & Durable
- For Interior Masonry in Damp Conditions
- Discourages Dirt Retention

PRODUCT INFORMATION

Typical Use

Suitable for use on interior masonry in damp conditions.

Pack Size

5L.

Colour Range

White only.

Film Properties

Chemical Resistance: Resistant to mild atmospheric fume attack and to the salts in new mortar, rendering and similar surfaces.

Heat Resistance: Not normally applied to heated surfaces.

Water Resistance: Resistant to the levels of atmospheric humidity present in cellars.

Film Thickness

Film thickness will be dependent on the coverage achieved.

Wet: 63 microns.

Dry: 33 microns.

Composition (nominal)

Pigment: Lightfast Pigments.

Binder: Acrylic Copolymer with Alkyd.

Solvent: White Spirit and Low Odour Aliphatic Hydrocarbons.

Volume Solids

53% (nominal).

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean, dry and free from all defective or poorly adhering material such as dirt, grease or wax. Remove and treat any mould, algae, lichen or moss with **Weathershield** Multi-Surface Fungicidal Wash*.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Surfaces which remain powdery and friable after thorough preparation should be sealed with a coat of **Dulux Trade** Alkali Resisting Primer.

Any surface defects should be filled with the appropriate **Polycell** Trade **Polyfilla**.

CELLAR PAINT

SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. The normal finishing process is 2 full coats of **Dulux Trade** Cellar Paint, but on previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient.

APPLICATION METHOD

Brush or roller only. Do not spray. When applying **Dulux Trade** Cellar Paint, unprotected food/drink products could be tainted and should be removed from the work area.

As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m² per litre.

Spray Recommendations

This product should not be sprayed.

Drying Times

Single coat at standard thickness:

Touch Dry: Dependent on temperature and humidity.

Recoat: 2-16 hours, although will vary according to temperature and humidity, and will be more in cold or damp conditions.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with brush cleaner.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

EU limit value for this product (cat.: A/i): 500g/l (2010). This product contains max. 420g/l VOC. VOC content: High (25-50%).

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

***Weathershield** Multi-Surface Fungicidal Wash contains: Benzalkonium Chloride.
Use biocides safely. Always read the label and product information before use.



Issued 02/14

503

CELLAR PAINT

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 503) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at duluxtrade.co.uk/pp

AkzoNobel