



MORDANT SOLUTION

Dulux Trade Mordant Solution chemically etches and prepares the surface of new, bright galvanised metal to provide adhesion for subsequent paint systems.

KEY BENEFITS

- New Galvanised Metal
- Chemically Etches Surfaces
- Water-Based

PRODUCT INFORMATION

Typical Use

Suitable for use on new galvanised metal.

Pack Size

2.5L.

Colour Range

Blue/Green Colour in container.

Film Properties

N/A.

Composition (nominal)

Solution of Phosphoric Acid and Copper Salt.

Volume Solids

N/A.

SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry) and free from all defective or poorly adhering material such as dirt, grease and wax.

Degrease where necessary with a suitable oil and grease remover. Rinse with clean water to remove residues.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

SYSTEMS INFORMATION

Apply a liberal coat of **Dulux Trade** Mordant Solution by brush and allow to dry. If the surface fails to turn black overall, the most likely cause is contamination of the surface or the presence of a factory applied pretreatment. Rinse the surface thoroughly and abrade, using a suitable abrasive paper. Remove all residues and re-apply **Dulux Trade** Mordant Solution. Avoid over-application as pooling of the wash will result in the formation of a fine brown deposit of copper.

After treatment the surface must be rinsed with clean water to remove all residues and then allowed to dry before priming.

The pre-treated surface should be overcoated with an appropriate **Dulux Trade** metal primer within 48 hours or before contamination can recur.

APPLICATION METHOD

Brush only. Do not spray.

Practical Coverage

N/A.

MORDANT SOLUTION

Spray Recommendations

This product should not be sprayed.

Drying Times

N/A.

Cleaning Up

After use, remove as much product as possible from equipment before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover

paint, please dispose of it responsibly. Find out more at duluxtrade.co.uk/pp.

Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

VOC

N/A.

FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:0333 222 70 70).

Always read full Health, Safety & Environmental Information on can before use.

Safety datasheet (SDS 509) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting duluxtrade.co.uk.

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.