

Dulux TRADE

TRACKER PAINT FROM DULUX TRADE

Issued May 2006

514

PRODUCT INFORMATION

Typical Use	<p>Tracker Paint from Dulux Trade is an interior matt emulsion that utilises new SMARTEC technology to make decorating simpler and faster whilst ensuring that excellent results are achieved. It includes revolutionary TRACKER technology to help you see areas that you have painted, even in difficult lighting conditions, by applying pink but fading to white in under an hour. Tracker Paint from Dulux Trade has excellent coverage and requires only one coat over previously decorated white surfaces.</p> <p>Before preparing any surface for painting, read the Safety, Health & Environmental information on page 2 about old lead-based paints.</p>
Pack Size	5 and 10 litre.
Colour Range	N/A.
Film Properties	<p>Chemical Resistance: Not suitable.</p> <p>Heat Resistance: Not suitable for use on heated surfaces eg radiators.</p> <p>Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand moderate washing. Where frequent heavy condensation is likely, as in some kitchens and bathrooms, Dulux Trade Diamond Quick Drying Eggshell is more suitable.</p>
Composition (nominal)	<p>Pigment: Lightfast Non-Lead Pigments.</p> <p>Binder: Acrylic Copolymer Emulsion.</p> <p>Solvent: Water.</p>
Volume Solids	White 33% (nominal), other colours will vary.
Application Method	Brush, roller or spray.
Drying Times	<p><i>Single coat at standard thickness:</i></p> <p>Touch Dry: Dependent upon temperature and humidity.</p> <p>Recoat: 4-6 hours.</p>
Practical Coverage	A guide to the practical coverage which can be achieved under normal conditions is up to 13m ² / litre.
Thinning	<p>Sealing new or bare surfaces: Add up to 1 part clean water to 5 parts paint.</p> <p>Conventional spray application: Add up to 1 part clean water to 2.5 parts paint.</p> <p>Airless spray application: Add up to 1 part clean water to 5 parts paint.</p>
Spray Recommendations	<p>Conventional Spray: Satisfactory through most equipment.</p> <p>Airless Spray: A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.</p>
Cleaning Up	After use, remove as much paint as possible from brushes before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

SURFACE PREPARATION

Surfaces must be clean and dry before painting.
Remove all loose and defective paint.
Where necessary wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.
Where necessary, rub down and then wipe off with a damp, lint free cloth, to avoid dust.
Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

SYSTEM INFORMATION

Stir thoroughly before use.

The product turns from pink to white in less than 60 minutes. This can be extended by on-site conditions. Where a second coat of **Tracker** Paint from **Dulux Trade** is required, allow a minimum of 4 hours between coats.

Avoid high condensation for the first 7 days after application as this may result in the temporary re-appearance of the pink colour, but this will fade back to white after about 60 minutes.

Porous surfaces including previously unpainted patterned textured surfaces such as Artex and paintable wallcoverings can affect the fade time.

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

WATER-BASED PAINT

Ensure good ventilation during application and drying.

Do not breathe spray. When spraying inside, wearing a cartridge mask of Assigned Protection Factor 40 x OEL for particulates is recommended.

Avoid contact with skin and eyes.

When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Safety data sheet available for professional user on request. This includes waste hazard categories.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints, Wexham Road, Slough, SL2 5DS.

Tel: 0870 242 1100 (national call rates apply)

EU limit value for this product (cat A/a) : 75g/l (2007) / 30g/l (2010)

This product contains max. 25g/l VOC

See www.duluxtrade.co.uk

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, SMARTEC, TRACKER, Polycell, Polyfilla and the ICI Roundel are trademarks of ICI.

© ICI 06 (240506IT).

