



# ULTRA MATT

**Dulux Trade** Ultra Matt is specially formulated to provide a dead matt, non-reflective finish in all angles, this product is ideal for ceilings. **Dulux Trade** Ultra Matt has excellent touching-in properties, providing near invisible touch-up for areas in critical lighting.

## KEY BENEFITS

- Non-Reflective
- Ideal for Ceilings in Critical Lighting
- Excellent Touching-In Properties

## PRODUCT INFORMATION

### Typical Use

Suitable for use on all normal interior wall and ceiling surfaces.

### Pack Size

10L.

### Colour Range

White only

### Composition (nominal)

**Pigment:** Lightfast pigments

**Binder:** Copolymer binder

**Solvent:** Water

### Volume Solids

33.6% (nominal).

## SURFACE PREPARATION

To get the best results, ensure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell Trade Polyfilla**.

## SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a first coat of **Dulux Trade Drywall Primer Sealer**. The normal finishing process is 2 or 3 full coats of **Dulux Trade Ultra Matt**, but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient.

# ULTRA MATT

## APPLICATION METHOD

Brush, roller, conventional or airless spray.

As with all water-based paints, do not apply at temperatures below 8°C (as recommended by British Standard BS 6150).

## Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 16m<sup>2</sup> per litre.

## Thinning

Thinning not required.

## Spray Recommendations

**Conventional Spray:** Satisfactory through most equipment.

**Airless Spray:** A typical set up for airless spray would be a minimum working pressure on paint of 138 bars (2000lb/sq in) with a spray tip size of 0.43-0.48mm (17-19 thou) and a spray tip angle of 40°.

## Drying Times

*Single coat at standard thickness:*

**Touch Dry:** Dependent on temperature and humidity.

**Recoat:** 4 hours.

## Cleaning Up

After use, remove as much product as possible from brushes before cleaning with water.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to **Community RePaint**. Find out more at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp).

## Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

## VOC

EU limit value for this product (cat.: A/a): 30g/l (2010). This product contains max. 1g/l VOC. VOC content: Minimal (0-0.29%).

## FURTHER SUPPORT

If you need further support, please contact the **AkzoNobel** Technical Advice Centre on [0333 222 70 70](tel:03332227070).

**Always read full Health, Safety & Environmental Information on can before use.**

Safety datasheet (SDS 549) is available free on request by telephoning the **AkzoNobel** Technical Advice Centre or by visiting [duluxtrade.co.uk](http://duluxtrade.co.uk).



Issued 02/14

549

# ULTRA MATT

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp)

**AkzoNobel**