

DULUX TRADE QUICK DRYING WOOD DYE

617

PRODUCT INFORMATION

Typical Use	<p>Dulux Trade Quick Drying Wood Dye is a convenient way to transform bare wood. The rich woodshades resist fading and enhance the natural grain of the wood. An even, consistent colour is easily achieved. The self-sealing finish does not normally require varnishing. The low odour formula is touch dry in 30 minutes ensuring rapid job completion. It is suitable for use on softwoods, hardwoods and plywood.</p> <p>Before preparing any surface for painting, read the Safety, Health & Environmental information on page 2 about old lead-based paints.</p>
Pack Size	500ml.
Colour Range	See Dulux Trade brochures and colour chart.
Composition (nominal)	<p>Pigment: Blend of pigments.</p> <p>Binder: Acrylic resin.</p> <p>Solvent: Water-Based</p>
Volume Solids	Not determined.
Thinning	This product does not require thinning.
Application Method	A sponge or clean soft cloth.
Drying Times	<p><i>Single coat at standard thickness:</i></p> <p>Touch Dry: 30 minutes.</p> <p>Recoat: 2 hours.</p>
Practical Coverage	On new / bare wood a litre of wood dye is sufficient to apply one coat to an area of up to 18m ² .
Cleaning Up	<p>After use, remove as much wood dye as possible from equipment before cleaning with clean water.</p> <p>Do not use or store in extremes of temperature and protect from frost.</p>

SURFACE PREPARATION

Apply to bare wood only. Surfaces must be sound, clean and dry before treating. Completely remove all existing coatings. Sand to a smooth finish.

Clean off any wax polish, grease or finger marks with white spirit.

HOW TO USE

SHAKE WELL FOR ONE MINUTE BEFORE USE AND OCCASIONALLY DURING USE.

Try a test area first. Using a sponge or clean soft cloth, apply with a firm sweeping motion. Avoid overlap. Finish off in the direction of the grain to give an even colour. Two coats are normally sufficient for most wood. Allow to dry for 2 hours between coats. If deeper colour is required, apply further coats. Do not apply below 5°C or in high humidity. Protect from water or steam for 2-3 days after application.

Varnish is not normally required, but on areas of wear, eg. floors, dry for 24 hours and finish with **Diamond Glaze** from **Dulux Trade** or other appropriate varnish.

SAFETY, HEALTH & ENVIRONMENTAL INFORMATION

WATER-BASED WOOD DYE

Ensure good ventilation during application and drying.

Avoid contact with skin and eyes. When painting it is advisable to wear eye protection. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children. Do not empty into drains or watercourses.

Safety data sheet available for professional user on request. This includes waste hazard categories.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints, Wexham Road, Slough SL2 5DS.

Tel: 0870 242 1100 (national call rates apply)

EU limit value for this product (cat. : A/e) : 150 g/l (2007)/130 g/l (2010)

This product contains max. 15 g/l VOC

See www.duluxtrade.co.uk

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, Diamond Glaze and the ICI Roundel are Trademarks of ICI.

© ICI 07 (070307IT)