



# CUPRINOL TRADE QUICK DRYING CLADDING AND FENCE OPAQUE FINISH

**CT693**

## PRODUCT INFORMATION

<b>Typical Use</b>	<p><b>Cuprinol Trade</b> Quick Drying Cladding and Fence Opaque Finish is a high performance water-based opaque exterior woodstain for the protection and decoration of exterior non-joinery timber such as cladding, garden structures and rough sawn or smooth fencing.</p> <p>Before preparing any surface for painting, read the Health Safety &amp; Environmental information on page 2 about old lead-based paints.</p>
<b>Codes according to the List of Wastes Regulations</b>	<p>Product as supplied: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11.</p> <p>Part-used containers, containing dried residues of the supplied product: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11</p> <p>Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.</p> <p>"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.</p> <p>These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.</p>
<b>Pack Size</b>	10 litre only.
<b>Colour Range</b>	See appropriate <b>Cuprinol Trade</b> colour card.
<b>Composition (nominal)</b>	<p><b>Pigment:</b> Titanium dioxide, iron oxides and organic pigments.</p> <p><b>Binder:</b> Vinyl acetate co-polymer.</p> <p><b>Solvent:</b> Water.</p>
<b>Volume Solids</b>	Nominal 47%.
<b>Application Method</b>	Brush, roller or spray, including the special <b>Cuprinol</b> Fence Sprayers.
<b>Drying Times</b>	<p><i>Single coat at standard thickness:</i></p> <p><b>Touch Dry:</b> 1-2 hours.</p> <p><b>Recoat:</b> 4 hours.</p>
<b>Practical Coverage (Typical)</b>	<p>Coverage will depend on the surface and application method:</p> <p><b>Brush:</b> Smooth planed wood: 6 sq m / litre / coat</p> <p><b>Brush:</b> Rough sawn wood 3 sq m / litre / coat</p> <p><b>Sprayers:</b> Smooth planed wood: 6 sq m / litre / coat</p> <p><b>Sprayers:</b> Rough sawn wood: 4 sq m / litre / coat</p>
<b>Spray Recommendations</b>	<p><b>Conventional Spray:</b> Satisfactory through most equipment.</p> <p><b>Airless Spray:</b> A typical set up for airless spray application would be a minimum working pressure on paint of 133 bars (2000lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.</p>
<b>Cleaning Up</b>	After use, remove as much paint as possible from brushes before cleaning with clean water. Do not use or store in extremes of temperature and protect from frost.

# CUPRINOL TRADE QUICK DRYING CLADDING AND FENCE OPAQUE FINISH

# CT693

## SURFACE PREPARATION

Surfaces must be sound, clean and dry before treating.  
Remove all loose and defective coatings, if necessary stripping back to bare wood.

Remove and treat any mould, algae, lichen or moss with **\*\*Weathershield** Multi-Surface Fungicidal Wash.

Thoroughly rub down all surfaces in the direction of the grain to remove any grey, weathered wood and surface sheen from remaining coatings, and then dust off (refer to your COSHH Assessment).

## SYSTEM INFORMATION

**Stir thoroughly before and during use.**

Two coats of **Cuprinol Trade** Quick Drying Cladding and Fence Opaque Finish will normally be required to produce a completely opaque finish. Allow the first coat to dry before applying the second. Allow up to 4 hours between coats.

Do not apply below 5°C, in damp conditions or if rain or frost is likely before the finish is fully dry.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

### WATER-BASED WOODSTAIN

**THIS PRODUCT IS FOR EXTERIOR USE ONLY.**

**Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**

Ensure good ventilation during application and drying.

Do not breathe spray. When spraying in confined spaces, wearing a cartridge mask of Assigned Protection Factor 40 x OEL for particulates is recommended.

Avoid contact with skin and eyes.

When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook.

Do not empty into drains or water courses.

Avoid release to the environment. Refer to special instructions/Safety data sheet.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints Technical Group, at ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

See [www.cuprinoltrade.co.uk](http://www.cuprinoltrade.co.uk)

EU limit value for this product (cat.A/e):150g/l (2007)/130g/l (2010).

This product contains max.30g/l VOC

**\*\* Weathershield** Multi-Surface Fungicidal Wash contains:

Benzalkonium Chloride

Use biocides safely. Always read the label and product information before use.

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Cuprinol, ICI Roundel and Dulux Trade are Trademarks of AkzoNobel.

© AkzoNobel 2011 (150620111T SDSCT693)

