



CUPRINOL TRADE EXTERIOR WOOD PRESERVER^(BP)

CT702

PRODUCT INFORMATION

Typical Use	<p>Cuprinol Trade Exterior Wood Preserver^(BP) is an exterior pigmented wood preservative for rough sawn and smooth garden timbers, such as cladding, fencing, sheds, greenhouses and summerhouses. Cuprinol Trade Exterior Wood Preserver^(BP) contains active ingredients that penetrate into the timber to prevent rot, decay and blue stain. Cuprinol Trade Exterior Wood Preserver^(BP) is a water-based product that can be used near plants.</p> <p>Before preparing any surface for painting, read the Health, Safety and Environmental information on pages 2&3 about old lead-based paints.</p>
Codes according to the List of Wastes Regulations	<p>Product as supplied: Assigned as hazardous waste code 03 02 02* organochlorinated wood preservatives.</p> <p>Part-used containers, containing dried residues of the supplied product: Assigned as hazardous waste code 03 02 02* organochlorinated wood preservatives.</p> <p>Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging.</p> <p>"Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means.</p> <p>These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.</p>
Pack Size	2.5, 5 litre and 25 litre (for Professional users only).
Colour Range	<p>See appropriate Cuprinol Trade colour card.</p> <p>Note. The colour of treated wood may be affected by type and condition of wood and may be modified by previous treatments. If in doubt, try a small test area before using.</p>
Composition (nominal)	<p>Pigment: Iron oxide, carbon black and organic pigments.</p> <p>Binder: Acrylic Co-polymer Emulsion.</p> <p>Solvent: Water.</p>
Volume Solids	14% (nominal).
Application Method	Brush only.
Drying Times	<p>Touch Dry: 2 to 6 hours.</p> <p>Recoat: Allow the previous coat to soak in before applying the next.</p>
Practical Coverage	5 sq metres timber surface per litre.
Thinning	Do not thin.
Cleaning Up	<p>After use, remove as much product as possible from equipment before cleaning with clean water.</p> <p>Do not use or store in extremes of temperature and protect from frost.</p>

SYSTEM INFORMATION

Cuprinol Trade Exterior Wood Preserver^(BP) can be used on all types of bare wood, wood that has been previously pressure treated or wood that has been previously treated with a wood preservative (provided it has been allowed to weather). Ensure surface is clean, dry and free from any surface coating, mould or algae before use. Use pre-treated timber for in ground contact situations.

CUPRINOL TRADE EXTERIOR WOOD PRESERVER^(BP) CT702

Shake or stir thoroughly before use and frequently during use to ensure even colour.

After suitable preparation apply 2-3 coats of **Cuprinol Trade** Exterior Wood Preserver^(BP). For best coverage three coats are recommended.

Please note that the colour in the can may look different when dry. If colour is important try a small inconspicuous area first.

ADDITIONAL INFORMATION

During application avoid spilling, splashing or over-spraying onto surrounding areas since stains can be difficult to remove. Clean any splashes immediately with soap and water.

FINISHING OF TREATED TIMBER

Timber treated is not suitable for paint, varnish or woodstain finishes.

HORTICULTURE

Suitable for treatment of structural greenhouse timbers and timbers in close proximity with plants (not seed boxes). Extra thorough drying must be allowed under service conditions before introducing plants.

BEEHIVES

Not recommended.

METALS

This wood preservative has no effect on common metals and metal fittings can be used on treated wood.

HEALTH , SAFETY & ENVIRONMENTAL INFORMATION

STATUTORY CONDITIONS RELATING TO USE

WATER-BASED PRESERVATIVE FOR EXTERIOR USE ONLY.

FOR USE ONLY AS A WOOD PRESERVATIVE.

FOR USE ONLY BY PROFESSIONAL OPERATORS.

APPLICATION RATE: APPLY AT A RATE OF 1 LITRE OF PRODUCT PER 5 SQUARE METRES OF TIMBER SURFACE.

The (COSHH) Control of Substances Hazardous to Health Regulations 2002 may apply to the use of this product at work.

Engineering control of operator exposure must be used where reasonably practicable in addition to the items of personal protective equipment.

Wear suitable protective clothing and suitable gloves.

AVOID EXCESSIVE CONTAMINATION OF COVERALLS AND LAUNDRY REGULARLY.

However, engineering controls may replace personal protective equipment if a COSHH assessment shows that they provide an equal or higher standard of protection.

DO NOT CONTAMINATE FOODSTUFFS, EATING UTENSILS OR FOOD CONTACT SURFACES.

This material and its container must be disposed of in a safe way.

UNPROTECTED PERSONS AND ANIMALS SHOULD BE KEPT AWAY FROM TREATED AREAS FOR 48 HOURS OR UNTIL SURFACES ARE DRY.

COVER ALL WATER STORAGE TANKS before application.

REMOVE OR COVER ALL FISH TANKS AND BOWLS before application.

Do not contaminate ground, waterbodies or watercourses with chemicals or used container.

Avoid release to the environment. Refer to special instructions/Safety data sheet.

ALL BATS ARE PROTECTED UNDER THE WILDLIFE AND COUNTRYSIDE ACT 1981 AND WILDLIFE (NORTHERN IRELAND) ACT 1985. BEFORE TREATING ANY STRUCTURE USED BY BATS, CONSULT NATURAL ENGLAND, SCOTTISH NATURAL HERITAGE, THE COUNTRYSIDE COUNCIL FOR WALES OR THE DEPARTMENT OF THE ENVIRONMENT FOR NORTHERN IRELAND.

READ ALL PRECAUTIONS BEFORE USE. HSE Number 9041.

PRECAUTIONS

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains 3-iodo-2-propynyl-N-butyl carbamate, propiconazole. May produce an allergic reaction.

WASH ANY CONTAMINATION from skin or eyes immediately.

WASH HANDS AND EXPOSED SKIN before meals and after use.

Keep only in the original container.

Keep container tightly closed.

KEEP IN A SAFE PLACE.

Keep out of the reach of children.

Contains: PROPICONAZOLE 0.24% w/w (2.5 g/l), 3-iodo-2-propynyl-N-butyl carbamate 0.95% w/w (9.9 g/l).

3-iodo-2-propynyl-N-butyl carbamate is a carbamate compound which has weak anticholinesterase activity.

DO NOT USE if under medical advice not to work with anticholinesterase compounds.

To avoid risks to man and the environment, comply with the instructions for use.

This product is approved under The Control of Pesticides Regulations 1986 (as amended) for use as directed. HSE Number 9041.

When applying it is advisable to wear eye protection.

Do not use or store by hanging on a hook.

Avoid the inhalation of dust. Wear suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

EU limit value for this product (cat. : A/e) : 150g/l (2007)/130g/l (2010)

This product contains max. 75 g/l VOC

See www.cuprinoltrade.co.uk

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Cuprinol is a trademark of AkzoNobel Group of Companies.

© AkzoNobel 2011 (15062011IT SDSCT702)

