



Dulux Trade Ultra Grip Primer

About this product

Dulux Trade Ultra Grip Primer is a water-based two-pack primer, specially formulated to provide excellent adhesion for subsequent coats of paint, when applied to difficult substrates such as glazed ceramic wall tiles, laminates, glass, anodised aluminium, powder-coated steel and stove enamel surfaces. Suitable for interior and exterior use. Compatible with Dulux Trade paint systems.

Key Benefits

- ✓ Two pack primer
- ✓ For stove enamels, laminates, glass
- ✓ Excellent adhesion on problem surfaces
- ✓ Water-based

Technical Information

Touch dry	4-6 hours at 20°
Recoatable	Minimum 16 hours and maximum 7 days. Hard dry after 16 hours. Recoat within 7 days for optimum intercoat adhesion
Coverage	Up to 10m ² per litre
Thinning (normal use)	Water

Product Information

Composition
Water-based

Key Benefits

Two pack primer, For stove enamels, laminates, glass, Excellent adhesion on problem surfaces, Water-

based

Colour Range

Digital Default Colors (Web Only)

Pack size

200ML, 800ML

Application Method

Application : Brush or short pile roller only. For health and safety reasons related to all solvent-based paints, spray application is not recommended. STIR THOROUGHLY BEFORE USE. It is recommended that a small test area is applied before treating the entire surface to ensure compatibility. Finish with an appropriate Dulux Trade paint system. Mixing Ratio: supplied in correct proportions. Add all of the Activator to the Base container and mix thoroughly for at least 5 minutes, until the product is smooth and even. Do not mix part units. Badly activated or incorrectly mixed materials will affect performance and may cause early failure or discolouration. Thinning: ready to use when mixed. If required, add a maximum of 10% clean water to activated primer. Pot life: up to 6 hours at 20°C.