



Dulux Trade Plus Smooth & Protect +

White

About this product

Dulux Trade Plus Smooth & Protect+ is part 3 of the 3 part Dulux trade Plus Thermacoat+ system. It has been specially designed to provide a protective mid-coat for the Dulux Trade Plus Thermacoat+ system, providing a smooth, flat finish that can be painted with any suitable interior Dulux Trade emulsion.

Key Benefits

- ✓ Part 3 of Dulux Trade Plus Thermacoat+ system:protective mid-coat

Technical Information

Recoatable	12 hours
Coverage	1m ² per litre

Product Information

Composition

Water-based

Key Benefits

Part 3 of Dulux Trade Plus Thermacoat+ system:protective mid-coat

Colour Range

CUPRINOL Digital Default Colors (Web Only)

Pack size

5L

Application Method

We recommend reading the Dulux Trade Plus Smooth & Protect + Product Datasheet for full information

available free on request by telephoning 0333 222 70 70 (ROI 021 422 0222) or visiting duluxtrade.co.uk. Dulux Trade Plus Smooth & Protect+ is ready to use. Do not dilute. Wear gloves, dust mask, arm and eye protection. For use over Dulux Trade Plus Thermacoat+ and Dulux Trade Plus levelling Fleece. Using a plastic spatula or flat trowel gently apply a 1mm layer on top of dry Dulux Trade Plus Thermacoat+ and Dulux Trade Plus Levelling Fleece. Distribute evenly until a smooth , flat finish is achieved. Leave to dry (minimum 12 hours depending on conditions). Before lightly sanding with very fine (240+ Grit) sandpaper and paint with any suitable interior Dulux Trade emulsion. Tip: for best results thin first coat 9up to 1 part clean water to 10 parts paint) Please note the Dulux trade Plus Thermacoat+ system can take up to 7 days to fully cure and gain full strength. This product should not be used in areas where condensation is a problem eg kitchens and bathrooms