



Dulux Trade All Purpose Primer

00E55 / White

About this product

Dulux Trade All Purpose Primer is a solvent-based primer suitable for use on most wood, metal and masonry surfaces, both inside and outside. In certain circumstances, specialist primers will be required e.g. highly resinous wood, galvanised steel and new plaster.

Key Benefits

- ✓ For wood, metal and masonry
- ✓ Provides good adhesion
- ✓ Solvent-based

Technical Information

Touch dry	6 hours
Recoatable	After 6 hours
Coverage	Wood - up to 8m ² per litre, Metal - up to 11m ² per litre, Plaster - up to 7m ² per litre
Thinning (normal use)	10

Product Information

Composition
Solvent-based

Key Benefits
For wood, metal and masonry, Provides good adhesion, Solvent-based

Colour Range

WOLF WEB UK (Painter) Dulux Ready Mix

Pack size

1L, 2.5L

Application Method

Application: Brush or roller only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended. STIR THOROUGHLY BEFORE USE. Apply 1 coat of Dulux Trade All Purpose Primer to all bare areas. Apply 2 coats to badly rusted metal. Allow to dry for a minimum of 6 hours, then apply an appropriate Dulux Trade finishing system