



Dulux Trade Aluminium Wood Primer

About this product

Dulux Trade Aluminium Wood Primer is a solvent-based primer containing aluminium pigment suitable for use on all types of softwoods and hardwoods, inside and outside, especially those which are highly resinous. It can also be used as a sealer for aged creosoted or bitumen coated surfaces or as a first coat when using Dulux Trade Aluminium Paint on timber, where a two-coat aluminium system is required.

red.

Key Benefits

- ✓ Interior & Exterior Use
- ✓ For outstanding sealing properties
- ✓ For resinous & creosoted woods
- ✓ Solvent-based

Technical Information

Touch dry	3-4 hours
Recoatable	After 16-24 hours
Coverage	Up to 17m ² per litre

Product Information

Composition

Solvent-based

Key Benefits

Interior & Exterior Use, For outstanding sealing properties, For resinous & creosoted woods, Solvent-

based

Pack size

1L, 2.5L, 5L

Application Method

Application: Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended. **STIR THOROUGHLY BEFORE USE.** After suitable surface preparation apply 1 or 2 coats of Dulux Trade Aluminium Wood Primer. Apply 2 coats of Dulux Trade Aluminium Wood Primer over highly resinous wood or when using over aged creosote or bitumen coated surfaces. Allow up to 24 hours between coats (48 hours on aged creosote or bitumen coated surfaces). Finish with an appropriate Dulux Trade paint system.