



Dulux Trade High Gloss

DANCETIME

About this product

Dulux Trade High Gloss is a solvent-based formulation which offers excellent flow, giving surfaces a tough, durable high gloss finish. Suitable for use on interior and exterior wood and metal surfaces.

Key Benefits

- ✓ Tough durable finish
- ✓ Excellent flow
- ✓ Coverage up to 18m² per litre
- ✓ Solvent-based

Technical Information

Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 18m ² per litre
Thinning (normal use)	White Spirit 10

Product Information

Composition

Solvent-based

Key Benefits

Tough durable finish, Excellent flow, Coverage up to 18m² per litre, Solvent-based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019,

Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

1L, 2.5L, 5L

Application Method

Application : Brush or roller only. For health and safety reasons related to all solvent based paints, spray application is not recommended. STIR THOROUGHLY BEFORE USE. Apply 1 coat of the appropriate coloured Dulux Trade Undercoat, followed by 1 or 2 coats of Dulux Trade High Gloss. When a fast drying system is required for new work, Dulux Trade Quick Dry Wood Primer Undercoat (available in white only) can be used as an alternative. Allow a minimum of 6 hours for the undercoat to dry before applying the gloss finish. Where a second coat of Dulux Trade High Gloss is required, allow a minimum of 16 hours between coats.