



## Dulux Trade Satinwood

COSY CASHMERE

### About this product

Dulux Trade Satinwood is a solvent-based satin finish formulation that is tough, hardwearing and dirt resistant. Does not require an undercoat except where a strong colour change is required. Suitable for use on interior wood and metal surfaces.

### Key Benefits

- ✓ Tough, durable finish
- ✓ Self undercoating
- ✓ Dirt resistant
- ✓ Solvent-based

### Technical Information

Touch dry	4-6hours
Recoatable	16-24 hours
Coverage	Up to 17m <sup>2</sup> per litre
Thinning (normal use)	White Spirit 10

### Product Information

#### Composition

Solvent-based

#### Key Benefits

Tough, durable finish, Self undercoating, Dirt resistant, Solvent-based

#### Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

**Pack size**

1L, 2.5L, 5L

## Application Method

Application: Brush or roller only. For Health and Safety reason related to all solvent-based paints, spray application is not recommended. STIR THOROUGHLY BEFORE USE. The normal finishing process is 2 full coats of Dulux Trade Satinwood. However, where a strong colour change is required, then a coat of an appropriate coloured Dulux Trade Undercoat may be necessary. Whilst leading-edge technology has been used in the development of this product, the nature of white solvent-based paints means that they will all discolour over time. The rate of discolouration is faster on areas with no or low natural or UV light. For long-lasting whiteness, we recommend the use of a water-based formulation such as Dulux Trade Quick Dry Satinwood.