



Dulux Trade Vinyl Matt

69RB 70/114

About this product

A top quality high opacity emulsion based on unique AkzoNobel technology which gives excellent coverage for everyday living. With an improved in-can consistency, Dulux Trade Vinyl Matt gives a smooth flow for easy application and a high quality finish.* Suitable for all normal interior wall and ceiling surfaces.

*Compared with previous formulation pre-June 2017. Vinyl Matt Light & Space has not been upgraded

een upgraded

Key Benefits

- ✓ Excellent application and finish
- ✓ High opacity
- ✓ Coverage up to 17m² per litre
- ✓ Water-based

Technical Information

Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 17m ² per litre
Thinning (normal use)	Water 5

Product Information

Composition
Water-based

Key Benefits

Excellent application and finish, High opacity, Coverage up to 17m² per litre, Water-based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

1L, 2.5L, 5L, 10L

Application Method

Application : Brush,roller or spray. STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of Dulux Trade Vinyl Matt (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full coats of Dulux Trade Vinyl Matt but on previously painted surfaces in good condition where similar colours are used, 1 coat may be sufficient. For best colour consistency, purchase sufficient tinted paint for each job at one time from the same source.