



Dulux Trade Weathershield Exterior High Gloss

DH SLATE

About this product

Part 3, of a 3 part weather resistant and flexible paint system from Dulux Trade, specifically developed to give long-lasting, high gloss protection for exterior woodwork. Contains a fungicide to inhibit mould growth on the paint film and help it stay cleaner for longer. Provides 8 year weathering durability, when used as part of the full Weathershield exterior paint system.

Key Benefits

- ✓ 8 year all weather protection
- ✓ Tough and durable protection
- ✓ Contains a fungicide to help protect against the disfiguring effect of mould growths on its film
- ✓ Can be used on plastic gutters, pipes and primed metal such as garage doors
- ✓ Solvent based

Technical Information

Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 18m ² per litre
Thinning (normal use)	White Spirit 10

Product Information

Composition

Solvent-based

Key Benefits

8 year all weather protection, Tough and durable protection, Contains a fungicide to help protect against the disfiguring effect of mould growths on its film, Can be used on plastic gutters, pipes and primed metal such as garage doors, Solvent based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

1L, 2.5L, 5L

Application Method

Application: Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended. STIR THOROUGHLY BEFORE USE. Apply 2 coats of the appropriate coloured Weathershield Exterior Flexible Undercoat to all primed wood, followed by 1 coat of Weathershield Exterior High Gloss.