



Dulux Trade Weathershield Smooth Masonry Paint

BERRY BLAST

About this product

Dulux Trade Weathershield Smooth Masonry Paint is an exterior quality emulsion paint based on all acrylic resin. It contains a fungicide to inhibit mould growth on the paint film and help it stay cleaner for longer. It is particularly suitable for use in changeable weather and is shower resistant within 30 minutes after application.

Key Benefits

- ✓ 15 year all weather protection
- ✓ Shower resistant within 30 minutes
- ✓ Excellent opacity
- ✓ Water-based

Technical Information

Touch dry	30 minutes
Recoatable	After 2-4 hours dependent on temperature and humidity
Coverage	Up to 16m ² per litre
Thinning (normal use)	Water 5

Product Information

Composition
Water-based

Key Benefits

15 year all weather protection, Shower resistant within 30 minutes, Excellent opacity, Water-based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

2.5L, 5L

Application Method

Application: Brush, roller or spray. STIR THOROUGHLY BEFORE USE. Seal all new or bare surfaces with a thinned coat of Weathershield Smooth Masonry Paint (up to 1 part clean water to 5 parts paint). The normal finishing process is 2 full coats of Weathershield Smooth Masonry Paint, but on previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient. In normal conditions two coats of Weathershield Smooth Masonry Paint properly applied to the substrate in accordance with the instructions will perform satisfactorily for up to 15 years giving good colour stability (as part of BBA certificate 97/3383). See current colour collateral for choice of colours.