



Dulux Trade Weathershield Stabilising Primer

About this product

Dulux Trade Weathershield Stabilising Primer is a solvent-based primer specially formulated to seal unstable areas which remain powdery and chalky after the surface has been thoroughly prepared for painting with Weathershield Masonry Paints.

Key Benefits

- ✓ Seals and stabilises
- ✓ For powdery masonry surfaces
- ✓ Ready for use
- ✓ Solvent-based

Technical Information

Touch dry	2-4 hours dependent on temperature and humidity
Recoatable	16-24 hours
Coverage	Up to 10m ² per litre
Thinning (normal use)	White Spirit

Product Information

Composition

Solvent-based

Key Benefits

Seals and stabilises, For powdery masonry surfaces, Ready for use, Solvent-based

Pack size

5L

Application Method

Application: Brush or roller only. For Health and Safety reasons related to all solvent-based paints, spray is not recommended. SHAKE CONTAINER VIGOROUSLY BEFORE USE. When the surface has been fully prepared any areas that remain powdery and chalky should be sealed with a coat of Weathershield Stabilising Primer. When fully dry apply 2 coats of the selected Weathershield Masonry Paint.

Weathershield Stabilising Primer should not be used as a general purpose sealer on normal or sound surfaces (i.e not powdery and chalky after the surface has been thoroughly prepared). New or sound bare surfaces should only be sealed with a thinned first coat of the masonry paint itself.