



## Dulux Trade Weathershield Textured Masonry Paint

### About this product

Dulux Trade Weathershield Textured Masonry Paint is an exterior quality fine texture emulsion paint based on an acrylic resin. Contains a fungicide to inhibit mould growth on the paint film. The formulation gives an attractive fine granular finish and allows a higher build.

### Key Benefits

- ✓ 10 year all weather protection
- ✓ Helps bridge fine cracks
- ✓ Coverage up to 8m<sup>2</sup> per litre
- ✓ Water-based

### Technical Information

Touch dry	1-2 hours
Recoatable	After 2-4 hours
Coverage	Up to 8m <sup>2</sup> per litre
Thinning (normal use)	Water

### Product Information

#### Composition

Water-based

#### Key Benefits

10 year all weather protection, Helps bridge fine cracks, Coverage up to 8m<sup>2</sup> per litre, Water-based

**Colour Range**

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandeck, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF UK ZXXX AE Collection 21 Painters, WOLF WEB UK (Painter) DT ProColourGuide 2018, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandeck, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

**Pack size**

5L

**Application Method**

Application: Brush, roller or spray. STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned coat of

Weathershield Textured Masonry Paint (up to 1 part water to 5 parts paint). The normal finishing process is 2 full coats of Weathershield Textured Masonry Paint, but on previously painted surfaces in good condition, where similar colours are used 1 coat may be sufficient.