



Dulux Trade Weathershield Maximum Exposure Smooth Masonry Paint

About this product

Dulux Trade Weathershield Maximum Exposure Smooth Masonry Paint Provides exterior durability and protection even in harsh and demanding environments, containing an added fungicide to inhibit mould growth on the paint film. The unique properties provide a tough and flexible paint film that is up to 5 times more flexible than conventional masonry paints, covering hairline cracks and preventing subse

quent cracking or flaking. Suitable for application to bare and previously painted surfaces, including solvent-based finishes. Shower resistant within 15 minutes of application.

Key Benefits

- ✓ 5 x more flexible than conventional masonry paints
- ✓ Adhesion promoted
- ✓ Salt/chemical spray resistant
- ✓ Shower resistant in 15 minutes
- ✓ Application down to 7deg C
- ✓ Fungicide to inhibit mould growth

Technical Information

Touch dry	30 minutes
Recoatable	After 2-4 hours dependent on temperature and humidity
Coverage	Up to 14m ² per litre
Thinning (normal use)	Water 5

Product Information

Composition

Water-based

Key Benefits

5 x more flexible than conventional masonry paints, Adhesion promoted, Salt/chemical spray resistant, Shower resistant in 15 minutes, Application down to 7deg C, Fungicide to inhibit mould growth

Colour Range

Armstead Colour Guide, BS4800, Colour Futures 2019, Colour Palette (5) Fandeck, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandeck, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

5L

Application Method

Application: Brush, roller or spray. STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of Weathershield Maximum Exposure Smooth Masonry (up to 1 part water to 5 parts paint). The normal finishing process is 2 full coats of Weathershield Maximum Exposure Smooth Masonry, but on previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient. Suitable for application to surfaces previously painted with masonry paint, including solvent-based finishes.