



## Dulux Trade Weathershield Maximum Exposure Smooth Masonry Paint

02C39 / PLUM

### About this product

Dulux Trade Weathershield Maximum Exposure Smooth Masonry Paint Provides exterior durability and protection even in harsh and demanding environments, containing an added fungicide to inhibit mould growth on the paint film. The unique properties provide a tough and flexible paint film that is up to 5 times more flexible than conventional masonry paints, covering hairline cracks and preventing subse

quent cracking or flaking. Suitable for application to bare and previously painted surfaces, including solvent-based finishes. Shower resistant within 15 minutes of application.

### Key Benefits

- ✓ 5 x more flexible than conventional masonry paints
- ✓ Adhesion promoted
- ✓ Salt/chemical spray resistant
- ✓ Shower resistant in 15 minutes
- ✓ Application down to 7deg C
- ✓ Fungicide to inhibit mould growth

## Technical Information

<b>Touch dry</b>	30 minutes
<b>Recoatable</b>	After 2-4 hours dependent on temperature and humidity
<b>Coverage</b>	Up to 14m <sup>2</sup> per litre
<b>Thinning (normal use)</b>	Water 5

## Product Information

### Composition

Water-based

### Key Benefits

5 x more flexible than conventional masonry paints, Adhesion promoted, Salt/chemical spray resistant, Shower resistant in 15 minutes, Application down to 7deg C, Fungicide to inhibit mould growth

### Colour Range

Armstead Colour Guide, BS4800, Colour Futures 2019, Colour Palette (5) Fandeck, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF UK ZXXX AE Collection 21 Painters, WOLF WEB UK (Painter) DT ProColourGuide 2018, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandeck, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

### Pack size

5L

## Application Method

Application: Brush, roller or spray. STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of Weathershield Maximum Exposure Smooth Masonry (up to 1 part water to 5 parts paint). The normal finishing process is 2 full coats of Weathershield Maximum Exposure Smooth Masonry, but on previously painted surfaces in good condition, where similar colours are used, 1 coat may be sufficient. Suitable for application to surfaces previously painted with masonry paint, including solvent-based finishes.