



Dulux Trade Pyroshield Durable Eggshell

AGED IVORY

About this product

Pyroshield Durable Eggshell from Dulux Trade is a water-based flame retardant finish that upgrades substrates of fire classification from Class 3 to Class O (tested to BS476, parts 6 and 7).

Key Benefits

- ✓ Flame retardant
- ✓ Upgrades fire classification BS476
- ✓ Highly durable smooth finish
- ✓ Water-based

Technical Information

Touch dry	Dependent on temperature and humidity
Recoatable	2-4 hours
Coverage	Up to 12m ² per litre
Thinning (normal use)	Water 5

Product Information

Composition

Water-based

Key Benefits

Flame retardant, Upgrades fire classification BS476, Highly durable smooth finish, Water-based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019,

Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

5L

Application Method

Application: Brush, roller or airless spray. STIR THOROUGHLY BEFORE USE. In order to achieve fire classification, apply 2 coats at 12m²/l (this equates to 2 coats at a film thickness of 85 microns each). Do not thin. For sealed surfaces it is recommended that the substrate is lightly abraded before application. Over some (sealed) surfaces it may not be possible to achieve the recommended spreading rate on the first coat, and more than two coats may be required to achieve sufficient film build. For use on walls and ceilings, over substrates such as plasterboard, plaster, cement render and blockwork. Not suitable for use over wood.