



## Dulux Trade Quick Dry Undercoat

58BB 12/390

### About this product

Dulux Trade Quick Dry Undercoat is part 1 of an advanced 2 part water-based, high gloss system, with excellent opacity and coverage. It is specifically designed to provide the best top coat finish with Dulux Trade Quick Dry Gloss, but can be used on all interior wood and metal.

### Key Benefits

- ✓ Excellent coverage
- ✓ Advanced water based technology
- ✓ Perfect for Dulux Trade Quick Dry Gloss
- ✓ Water-based

### Technical Information

Touch dry	Dependent on temperature and humidity
Recoatable	4-5 hours
Coverage	Up to 10m <sup>2</sup> per litre

### Product Information

#### Composition

Water-based

#### Key Benefits

Excellent coverage, Advanced water based technology, Perfect for Dulux Trade Quick Dry Gloss, Water-based

#### Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019,

Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

**Pack size**

1L, 2.5L, 5L

## Application Method

Application: Apply by brush, roller or spray. For best results use a good quality synthetic (nylon polyester) brush or a short pile synthetic/mohair roller designed for the application of water-based paints. STIR THOROUGHLY BEFORE USE. Apply 1 or 2 coats of Dulux Trade Quick Dry Undercoat , as required, followed by 1 or 2 coats of Dulux Trade Quick Dry Gloss. Where a strong colour change is involved, 2 coats will be required. Newly painted doors and windows should not be closed (tightly) until the paint is fully dry.