



Dulux Trade Quick Dry Gloss

VANILLA SKIES

About this product

Dulux Trade Quick Dry Gloss is part 2 of an advanced 2 part water-based, high gloss system that provides a smooth, durable top coat for use on both interior wood and metal.

Key Benefits

- ✓ High gloss finish
- ✓ Longer lasting whiteness
- ✓ Tough, durable finish
- ✓ Water-based

Technical Information

Touch dry	1-2 hours, dependent on temperature and humidity
Recoatable	4-6 hours
Coverage	Up to 12m ² per litre

Product Information

Composition

Water-based

Key Benefits

High gloss finish, Longer lasting whiteness, Tough, durable finish, Water-based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandeck, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandeck, Weathershield Professional Colour Guide

Pack size

1L, 2.5L, 5L

Application Method

Application: Brush, roller or spray. For best results use a good quality synthetic (nylon polyester) brush, designed for use with water-based paints. **STIR THOROUGHLY BEFORE USE.** Apply 1 or 2 coats of Dulux Trade Quick Dry Undercoat as required, followed by 1 or 2 coats of Dulux Trade Quick Dry Gloss. Where a strong colour change is involved 3 coats will be required. Newly painted doors and windows should not be closed (tightly) until the paint is fully dry.

Some rubber and plastics contain high levels of chemicals called plasticizers. When these are in contact with each other and other materials, such as paint, a chemical reaction can occur, which can make these surfaces feel tacky to touch. This particularly affects water-based acrylic paints.

This can mean that when a door seal is pressed against the door or door jam, the painted surface and the rubber seal may stick together. This is known as blocking and can happen even when the paint is fully dried and cured.

We recommend using rubber strips made from Ethylene Propylene Diene Monomer (EPDM) as door seals and draft excluders because they are less likely to be affected.

We make this very clear in our Site Work Instructions.

SW 7.02 Water-borne coatings

Water-borne coatings can be sensitive to rubber containing plasticisers such as flexible PVC strips.

The paint film may resolve due to these plasticisers and become sticky, it is advisable to replace such flexible strips for those made of EPDM rubber.

We recommend that you seek the manufacturer's advice regarding this problem.