



## Dulux Trade Weathershield Quick Dry Exterior Satin

DH PEARL COLOUR

### About this product

Dulux Trade Weathershield Quick Dry Exterior Satin is a water-based, mid-sheen finish which is part of a paint system specifically developed to give long lasting protection for exterior wood. Tests show that Weathershield Quick Dry Exterior Satin system will provide extensive protection for up to six years if correctly applied as per the instructions for use. Contains a fungicide to inhibit mould

growth on the paint film and help it stay cleaner for longer.

### Key Benefits

- ✓ 6 years all weather protection
- ✓ Tough and durable protection
- ✓ Coverage up to 20m<sup>2</sup> per litre
- ✓ Water based

### Technical Information

Touch dry	1-2 hours
Recoatable	2-4 hours
Coverage	Up to 20m <sup>2</sup> per litre
Thinning (normal use)	Water

### Product Information

#### Composition

Water-based

### **Key Benefits**

6 years all weather protection, Tough and durable protection, Coverage up to 20m<sup>2</sup> per litre, Water based

### **Colour Range**

Armstead Colour Guide, BS4800, Colour Futures 2019, Colour Palette (5) Fandeck, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandeck, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

### **Pack size**

1L, 2.5L

## **Application Method**

Application: Brush only. Do not spray. STIR THOROUGHLY BEFORE USE. Apply 1 coat of the appropriate coloured Weathershield Quick Dry Exterior Undercoat to all primed wood. Apply a second coat of Weathershield Quick Dry Exterior Undercoat overall, followed by 1 coat of Weathershield Quick Dry Exterior Satin. Where a strong colour change is involved, 2 coats may be required. Allow a minimum of 2 hours before overcoating Weathershield Quick Dry Exterior Undercoat.