



Armstead Trade Anti- Mould Vinyl Matt

About this product

Armstead Trade Anti-Mould Vinyl Matt is a professional quality, high opacity matt emulsion that inhibits the growth of mould and algae and minimises surface imperfections. Suitable for all normal interior wall and ceiling surfaces, especially those at risk of disfigurement due to mould growth.

Key Benefits

- ✓ Helps to reduce the growth of mould and algae
- ✓ Minimises surface imperfections
- ✓ Water based

Special Features

- ✓ High Opacity

Technical Information

Touch dry	1-2 hours
Recoatible	2-4 hours
Coverage	Up to 14m ² /litre
Thinning (normal use)	Water 10

Product Information

Typical Use

To get the best results with Armstead Trade Anti-Mould Vinyl Matt, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry). Treat any existing mould or organic growth with Weathershield Multi-Surface Fungicidal Wash from Dulux Trade. See Armstead Trade

Datasheet AM213 for full information before use, available free on request by telephoning 0333 222 7070 or visiting armsteadtrade.co.uk. Before surface preparation, read the adjacent information about old lead paints.

Composition

Water-based

Key Benefits

Helps to reduce the growth of mould and algae, Minimises surface imperfections, Water based

Colour Range

Armstead Colour Guide, BS4800, RAL Classic, WOLF WEB UK (Painter) Armstead Ready Mix

Pack size

5L

Application Method

STIR THOROUGHLY BEFORE USE. Apply 1 or 2 coats of Armstead Trade Anti-Mould Vinyl Matt. Coverage up to 14m²/l on smooth surfaces of average porosity. Touch Dry: 1-2 hours. Recoat: 2-4 hours. Drying time dependent upon temperature & humidity.