



Dulux Trade Weathershield Quick Dry Exterior Undercoat

S 0500-N / Pure Brilliant White

About this product

Dulux Trade Weathershield Quick Dry Exterior Undercoat is specifically formulated to be used with Weathershield top coats to provide longer lasting protection for exterior woodwork. Its water-based formulation is quick drying and offers great flexibility to help absorb the natural movement of wood. Provides 6 year all weather protection when used as part of the full Weathershield exterior paint system.

stem.

Key Benefits

- ✓ 6 year all weather protection
- ✓ Flexible formulation
- ✓ Coverage up to 16m² per litre
- ✓ Water-based

Technical Information

Touch dry	1-2 hours dependent on temperature and humidity
Recoatable	2-4 hours dependent on temperature and humidity
Coverage	Up to 16m ² per litre

Product Information

Composition

Water-based

Key Benefits

6 year all weather protection, Flexible formulation, Coverage up to 16m² per litre, Water-based

Colour Range

WOLF WEB UK (Painter) Dulux Ready Mix

Pack size

1L, 2.5L, 5L

Application Method

Application: Brush only. Do not spray. STIR THOROUGHLY BEFORE USE. Treat any knots in wood with an appropriate knotting solution. New or bare surfaces: Prime all bare wood with 2 coats of Weathershield Preservative Primer +(BP) followed by 2 coats of Weathershield Quick Dry Exterior Undercoat. Previously painted surfaces: 1 coat of Weathershield Quick Dry Exterior Undercoat. Finishing: Allow to dry for a minimum of 2 hours between coats, then apply the appropriate Weathershield topcoat.