



Dulux Trade Undercoat

About this product

Dulux Trade Undercoat is a solvent-based undercoat recommended for use with Dulux Trade High Gloss. Provides excellent opacity and its high sheen level contributes to exceptional gloss retention. Suitable for use on correctly prepared and primed interior and exterior wood and metal surfaces

Key Benefits

- ✓ Excellent opacity
- ✓ Great flow
- ✓ Coverage up to 17m² per litre
- ✓ Solvent-based

Technical Information

Touch dry	2-6 hours
Recoatable	After 6-16 hours
Coverage	Up to 17m ² per litre
Thinning (normal use)	White Spirit 10

Product Information

Composition

Solvent-based

Key Benefits

Excellent opacity, Great flow, Coverage up to 17m² per litre, Solvent-based

Colour Range

CUPRINOL Digital Default Colors (Web Only), WOLF WEB UK (Painter) Dulux Ready Mix

Pack size

1L, 2.5L, 5L

Application Method

Application : Brush or roller only. For health and safety reasons related to all solvent-based paints, spray application is not recommended. **STIR THOROUGHLY BEFORE USE.** Apply 1 coat of the appropriate coloured Dulux Trade Undercoat, followed by 1 or 2 coats of Dulux Trade High Gloss. Allow a minimum of 6 hours for the undercoat to dry before applying the Gloss finish. Where a second coat of Dulux Trade High Gloss is required, allow a minimum of 16 hours between coats.