



## Dulux Trade Anti Graffiti Primer

### About this product

Dulux Trade Anti Graffiti primer provides excellent adhesion on difficult surfaces which can then be overcoated with any Dulux Trade Emulsion followed by a coating of Dulux Trade Anti Graffiti Clear Coat. Dulux Trade Anti Graffiti Paint Clear Coat is a high performance water-based paint that is resistant to repeated washing, steam cleaning and solvent cleaning. It can be used where graffiti is a p

roblem or as a hygienic coating e.g. hospitals, industrial kitchens and food and drink processing industries.

### Key Benefits

- ✓ Extra Durability
- ✓ For use on bare or sealed surfaces
- ✓ Interior & exterior use
- ✓ Water-based

### Technical Information

Touch dry	4-6 hours at 20°
Recoatable	Minimum 16 hours
Coverage	Up to 10m <sup>2</sup> per litre

### Product Information

#### Composition

Water-based

#### Key Benefits

Extra Durability, For use on bare or sealed surfaces, Interior & exterior use, Water-based

**Pack size**

1L, 4L

## Application Method

Mixing Ratio: Supplied in correct proportions. Add all of the Activator to the Base container and mix thoroughly for at least 5 minutes, until the product is smooth and even. Do not mix part units. Badly activated or incorrectly mixed materials will affect performance and may cause early failure or discolouration.

Recommended Systems: STIR THOROUGHLY BEFORE USE. Primer: 1 coat of Dulux Trade Anti Graffiti Primer. Finish: 2 coats of Dulux Trade Diamond Eggshell/Matt followed by 1-2 Coats of Dulux Trade Anti-Graffiti Clear Coat. NOTE: Do not apply over underbound coatings e.g. distemper or non cross-linked flexible coatings e.g. Acrylated Rubber, Chlorinated Rubber. It is recommended that a small test area is applied before treating the entire surface to ensure compatibility. Pot Life; 2 hours (depending on prevailing conditions).