



Dulux Trade Acrylic Gloss

MELLOW BRICK

About this product

A professional quality, quick drying and high sheen finish with good flow and application properties. Good durability and resistance to yellowing ensure this product is suitable for use on interior wood and metal surfaces. For best results, use in conjunction with Dulux Trade Quick Dry Undercoat.

Key Benefits

- ✓ Lower embodied carbon
- ✓ Excellent flow & opacity
- ✓ High gloss
- ✓ Water-based

Technical Information

Touch dry	Dependent on temperature and humidity
Recoatable	6 hours
Coverage	Up to 16m ² per litre
Thinning (normal use)	Water 10

Product Information

Composition

Water-based

Key Benefits

Lower embodied carbon, Excellent flow & opacity, High gloss, Water-based

Colour Range

Armstead Colour Guide, BS4800, Colour Futures 2019, Colour Palette (5) Fandeck, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandeck, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

2.5L

Application Method

Application: Apply by brush, roller or spray. For best results use a good quality synthetic (nylon polyester) brush, designed for use with water-based paints. STIR THOROUGHLY BEFORE USE. Apply 1 or 2 coats of Dulux Trade Quick Dry Undercoat from Dulux Trade as required, followed by 1 or 2 coats of Acrylic Gloss from Dulux Trade. Where a strong colour change is involved 3 coats will be required. Newly painted doors and windows should not be closed (tightly) until the paint is fully dry.