



Dulux Trade High Performance Floor Paint

About this product

Dulux Trade High Performance Floor Paint is a water-based two-pack epoxy floor paint, suitable for high traffic areas. Its hard wearing properties make it suitable for both interior and exterior use. It offers excellent abrasion resistance on concrete and metal floors, drying to a highly durable mid-sheen finish.

Key Benefits

- ✓ Optimum performance
- ✓ Highly durable, 2 pack system
- ✓ For use in heavy commercial environments
- ✓ Water-based

Technical Information

Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 6m ² per litre

Product Information

Composition

Water-based

Key Benefits

Optimum performance, Highly durable, 2 pack system, For use in heavy commercial environments, Water-based

Colour Range

Pack size

1.78L, 3.22L

Application Method

Application: Brush or roller only, do not spray. Mixing Ratio: Supplied in correct proportions. Add all of this Base to the Activator container and mix thoroughly for at least 5 minutes using a jiffy paddle in an electric drill, until the product is smooth and even. Do not mix part units. Badly activated or incorrectly mixed materials will affect performance and may cause early failure or discolouration. The mixed product should be allowed to stand for 5 minutes before application commences. Once started, application should continue without a break, cutting in where necessary as the application proceeds.

Pot Life: Up to 1 hour at 15°C. Up to 45 minutes at 23°C. Poor adhesion will result if product is thinned and used after pot life times.