



Armstead Trade Anti Slip Floor Paint

About this product

Armstead Trade Anti-Slip Floor Paint is a professional quality, ready-mixed anti-slip floor coating that provides a consistent textured finish. Suitable for interior and exterior use on concrete, wood and metal surfaces. Particularly suited for access ramps, staircases, walkways, etc.

Key Benefits

- ✓ Textured protective floor finish
- ✓ Reduces the risk of slipping
- ✓ Ideal for ramps, staircases and walkways
- ✓ Solvent based

Special Features

- ✓ Excellent coverage

Technical Information

Touch dry	1 hour
Recoatable	6 hours
Coverage	Up to 8m ² /litre

Product Information

Typical Use

To get the best results with Armstead Trade Anti-Slip Floor Paint, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry). See Armstead Trade Datasheet AM306 for full information before use, available free on request by telephoning 0333 222 7070 or visiting

armsteadtrade.co.uk. Before surface preparation, read the adjacent information about old lead paints.

Composition

Solvent-based

Key Benefits

Textured protective floor finish, Reduces the risk of slipping, Ideal for ramps, staircases and walkways,
Solvent based

Colour Range

Armstead Colour Guide, BS4800

Pack size

5L

Application Method

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of Armstead Trade Floor Paint (up to 1 part white spirit to 10 parts paint). The normal finishing process is 2 full coats of Armstead Trade Anti-Slip Floor Paint. Touch dry: 1 hour. Recoat: 6 hours. Useable in 48 hours. Drying times will be extended at low temperature. Full hardness is not reached for 7 days. Try to avoid excessive wear and tear during this period. Coverage: up to 8m²/l on smooth surfaces of average porosity.