



## Armstead Trade Stabilising Primer

### About this product

Armstead Trade Stabilising Primer is a professional quality, clear solvent-based primer. It is formulated to seal powdery exterior masonry surfaces and can be used with most decorative finishes.

### Key Benefits

- ✓ Seals porous, dry & powdery surfaces
- ✓ Resists alkali attack
- ✓ Use with Armstead Trade Masonry finishes
- ✓ Solvent based

### Special Features

- ✓ Excellent coverage

### Technical Information

Touch dry	2-4 hours
Recoatable	16-24 hours
Coverage	Up to 10m <sup>2</sup> /litre

### Product Information

#### Typical Use

To get the best results with Armstead Trade Stabilising Primer, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry). See Armstead Trade Datasheet AM301 for full information before use, available free on request by telephoning 0333 222 7070 or visiting

armsteadtrade.co.uk. Before surface preparation, read the adjacent information about old lead paints.

### **Composition**

Water-based

### **Key Benefits**

Seals porous, dry & powdery surfaces, Resists alkali attack, Use with Armstead Trade Masonry finishes,  
Solvent based

### **Pack size**

5L

## **Application Method**

STIR OR SHAKE THOROUGHLY BEFORE USE. After suitable preparation, the normal recommendation is to apply one coat of Armstead Trade Stabilising Primer to powdery surfaces, followed by the appropriate Armstead Trade finishing system. Touch dry: 8-12 hours. Recoat: 16-24 hours. These times will be significantly longer in cold damp conditions