



## Hammerite Red Oxide Primer

### About this product

Hammerite Red Oxide Primer is specially formulated for use on both bare and rusty iron and steel. For aluminium, galvanised and all other non-ferrous metals, use Hammerite Special Metals Primer

### Key Benefits

- ✓ A high performance anticorrosive formulation
- ✓ Quick drying.
- ✓ Can be used inside or outside
- ✓ Use on gates, railings and metal drainpipes
- ✓ Solvent based

### Special Features

- ✓ A high performance anticorrosive formulation
- ✓ Quick drying

### Technical Information

Touch dry	2 hours
Recoatable	6 hours
Coverage	12m <sup>2</sup> per litre

### Product Information

#### Typical Use

All surfaces must be clean and dry. Remove loose rust, scale and paint with a wire brush then rub down

with coarse abrasive paper to provide a firm surface. Abrade bare steel with coarse abrasive paper. Degrease all surfaces with Hammerite Brush Cleaner & Thinners and allow to dry

### **Composition**

Solvent-based

### **Key Benefits**

A high performance anticorrosive formulation, Quick drying,, Can be used inside or outside, Use on gates,railings and metal drainpipes, Solvent based

### **Pack size**

250ML, 500ML

## **System Information**

Stir paint thoroughly. For best results when applying by roller, use a short pile mohair roller. Apply 2 coats of Hammerite Red Oxide Primer, allowing a minimum of 6 hours between coats. A topcoat may be applied after a minimum of 6 hours. For best results, allow 24 hours. Hammerite Red Oxide Primer can be overpainted with most paints.

## **Application Method**

Stir paint thoroughly. For best results when applying by roller, use a short pile mohair roller. Apply 2 coats of Hammerite Red Oxide Primer, allowing a minimum of 6 hours between coats. A topcoat may be applied after a minimum of 6 hours. For best results, allow 24 hours. Hammerite Red Oxide Primer can be overpainted with most paints.