



## Hammerite Radiator Paint Satin

### About this product

Hammerite Radiator Paint is specially formulated to provide a heat resistant, brilliant white finish on domestic radiators and hot water pipes. Provides a tough long lasting finish

### Key Benefits

- ✓ For domestic water - filled radiators and pipes
- ✓ Resists yellowing
- ✓ Prevents rust
- ✓ Easy to use
- ✓ Low odour
- ✓ Solvent based

### Special Features

- ✓ Long lasting satin finish
- ✓ Tough & durable

### Technical Information

Touch dry	4-6 hours
Recoatable	16 hours
Coverage	7m <sup>2</sup> per litre

### Product Information

#### Typical Use

All surfaces must be clean, dry and free from rust, flaking paint, dirt, dust and grease. Rub down all painted surfaces with abrasive paper. Radiators must be turned off and only painted when cold

### **Composition**

Solvent-based

### **Key Benefits**

For domestic water - filled radiators and pipes, Resists yellowing, Prevents rust, Easy to use, Low odour, Solvent based

### **Pack size**

500ML

## **System Information**

Stir thoroughly before use. Apply 1 or 2 coats. For best results apply 2 coats. Allow 16 hours between coats. After application leave the radiator turned off for a minimum of 12 hours. Rooms should be well ventilated for 12 hours after the heating is turned on to help remove all paint odours.

## **Application Method**

Stir thoroughly before use. Apply 1 or 2 coats. For best results apply 2 coats. Allow 16 hours between coats. After application leave the radiator turned off for a minimum of 12 hours. Rooms should be well ventilated for 12 hours after the heating is turned on to help remove all paint odours.