



Sikkens Cetol BL Unitop

About this product

Cetol BL Unitop is a water-borne acrylic urethane varnish which provides a satin finish.

Key Benefits

- ✓ Excellent resistance to knocks, spillages and abrasion
- ✓ Non-yellowing
- ✓ Low odour
- ✓ Quick drying

Special Features

- ✓ Durable

Technical Information

Touch dry	2 hours
Recoatable	5 hours
Coverage	12-18 m ² /L

Product Information

Composition

Water-based

Key Benefits

Excellent resistance to knocks, spillages and abrasion, Non-yellowing, Low odour, Quick drying

Pack size

Application Method

Conditions: Do not apply when air/substrate temperatures are below 8°C or above 25°C during application or drying periods. Protect from frost until dry. Failure to meet these requirements may adversely affect the drying, visual quality and durability of the finish. Ensure product is thoroughly stirred before and during application, otherwise sheen variations may be experienced. Cetol BL Unitop is supplied ready for use. Do not thin.

For best results use a good quality synthetic-fibre brush specifically designed for the application of water-borne products. Apply the product in a full flowing coat, laying off in the direction of the grain, using the minimum number of brushstrokes required to produce an even finish. Avoid overbrushing, which creates brushmarks and will reduce the protection afforded.

This initial coat should satisfy the porosity/absorption of the timber. Carefully denib the first coat using a fine grade nylon abrasive pad or a fine grade (P240 or finer) wet or dry silicon carbide abrasive paper. Remove all dust. Three coats of Cetol BL Decor should be applied, allowing a minimum of 5 hours drying time between coats or a two coat application onto a coloured coating such as Cetol BL Decor for protection.