



## Dulux Trade Weathershield Quick Dry Exterior Gloss

### About this product

Dulux Trade Weathershield Quick Dry Exterior Gloss is a water-based gloss finish which is part of a paint system specially developed to give long lasting protection to exterior wood. The Weathershield Quick Dry Exterior Gloss system will provide extensive protection for up to six years if correctly applied as per the instructions for use. Contains a fungicide to inhibit mould growth on the paint f

ilm and help it stay cleaner for longer.

### Key Benefits

- ✓ 6 year all weather protection
- ✓ Tough & durable protection
- ✓ Coverage up to 16m<sup>2</sup> per litre
- ✓ Water-based

### Technical Information

|            |                                  |
|------------|----------------------------------|
| Touch dry  | 2 hours                          |
| Recoatable | 4 hours                          |
| Coverage   | Up to 16m <sup>2</sup> per litre |

### Product Information

#### Composition

Water-based

#### Key Benefits

6 year all weather protection, Tough & durable protection, Coverage up to 16m<sup>2</sup> per litre, Water-based

### **Colour Range**

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK CF20, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

### **Pack size**

1L, 2.5L, 5L

## **Application Method**

Application: Brush only. Do not spray. STIR THOROUGHLY BEFORE USE. Prime all bare wood with 2 coats of Weathershield Preservative Primer +(BP) followed by 1 coat of the appropriate coloured Weathershield Quick Dry Exterior Undercoat. Finish with 2 coats of Weathershield Quick Dry Exterior Gloss. Where a special process colour is to be used or a strong colour change is required, additional coats will be required (see appropriate Dulux Trade colour card). Allow a minimum of 2 hours before overcoating Weathershield Quick Dry Exterior Undercoat. Allow up to 4 hours before applying a second coat of Weathershield Quick Dry Exterior Gloss.