



Dulux Trade Metalshield Satin

18B21 / TIDEWAY

About this product

Metalshield Satin specially formulated with a quick drying formation that can be over coated within 4-6 hours. It provides protection against corrosion on ferrous and non-ferrous metal substrates such as railings, garage doors, lift shafts, staircases and emergency exit routes. *Applying our straightforward single-pack system: an appropriate Metalshield primer from Dulux Trade and 2 coats of Metal

shield Satin from Dulux Trade will deliver up to 8 years metal protection.

Key Benefits

- ✓ 8 year protection*
- ✓ High performance protection for metal
- ✓ For ferrous & non-ferrous metals
- ✓ Solvent-based

Technical Information

Touch dry	1-2 hours
Recoatable	4-6 hours
Coverage	Up to 13m ² per litre

Product Information

Composition
Solvent-based

Key Benefits

8 year protection*, High performance protection for metal, For ferrous & non-ferrous metals, Solvent-based

Colour Range

Armstead Colour Guide, BS4800, CUPRINOL Digital Default Colors (Web Only), Colour Futures 2019, Colour Palette (5) Fandek, Colour Wall In Store, Dulux Trade Commercial Colour Guide, Dulux Trade Professional Colour Guide, Heritage, RAL Classic, WOLF UK DX TRD ARCHIVE, WOLF WEB UK (Painter) Dulux Ready Mix, Weathershield 420 Fandek, Weathershield Professional Colour Guide Masonry, Weathershield Professional Colour Guide Trim

Pack size

2.5L, 5L

Application Method

Application : Brush or roller only. For health and safety reasons related to all solvent based paints, spray application is not recommended. STIR THOROUGHLY BEFORE USE. Apply 1 coat of the appropriate Metalshield primer followed by 2 coats of Metalshield Satin from Dulux Trade. Where a special process colour is to be used, or where a strong colour change is required, additional coats will be needed (see appropriate Dulux Trade colour card).