



Hammerite Garage Door Paint

About this product

Hammerite Garage Door Paint is a tough, durable and decorative high gloss finish specially formulated for use on garage doors

Key Benefits

- ✓ Tough and durable gloss finish for metal and wooden garage doors
- ✓ Highly resistant to flaking and discolouration
- ✓ Solvent based

Special Features

- ✓ Reduces runs when applied to vertical surfaces
- ✓ Tough, durable high gloss finish for metal and wooden garage doors

Technical Information

Touch dry	4 hours
Recoatable	16 hours
Coverage	8m ² per litre

Product Information

Typical Use

To get the best results ensure surface is dry and free from rust,millscale,paint,oil and grease. Lightly abrade painted surfaces with a suitable abrasive paper and if necessary a wire brush to remove rust. Degrease where necessary with white spirit. Prime bare aluminium or galvanised steel with Hammerite Special Metals Primer. On areas of bare or rusty steel apply a suitable metal primer. For best results use Hammerite No1. Rustbeater

Composition

Key Benefits

Tough and durable gloss finish for metal and wooden garage doors, Highly resistant to flaking and discolouration, Solvent based

Pack size

750ml

System Information

An ideal application temperature range is 8-25°C. Lightly stir before use. Do not mix vigorously. Apply 1 or 2 coats of Hammerite Garage Door Paint, depending on colour. Where a strong colour change is required, 2 or more coats will be required. Allow to dry overnight before applying a second coat.

Application Method

An ideal application temperature range is 8-25°C. Lightly stir before use. Do not mix vigorously. Apply 1 or 2 coats of Hammerite Garage Door Paint, depending on colour. Where a strong colour change is required, 2 or more coats will be required. Allow to dry overnight before applying a second coat.