



Armstead Trade Floor Paint

00A13 / GREYFRIAR

About this product

Armstead Trade Floor Paint is a professional quality, solvent-based, general purpose floor paint that delivers a touch and durable smooth floor finish. Suitable for use on interior concrete, wood and metal surfaces. Resistant to foot traffic and light rubber-wheeled vehicular traffic.

Key Benefits

- ✓ Tough & durable smooth floor finish
- ✓ Resistant to foot traffic
- ✓ For light industrial use
- ✓ Solvent based

Special Features

- ✓ Durable

Technical Information

Touch dry	4-6 hours
Recoatable	16-24 hours
Coverage	Up to 16m ² /litre
Thinning (normal use)	White Spirit 10

Product Information

Typical Use

To get the best results with Armstead Trade Floor Paint, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry). See Armstead Trade Datasheet AM305 for full information before use, available free on request by telephoning 0333 222 7070 or visiting armsteadtrade.co.uk. Before surface preparation, read the adjacent information about old lead paints.

Composition

Solvent-based

Key Benefits

Tough & durable smooth floor finish, Resistant to foot traffic, For light industrial use, Solvent based

Colour Range

Armstead Colour Guide, BS4800, RAL Classic

Pack size

5L

Application Method

STIR THOROUGHLY BEFORE USE. Seal new or bare surfaces with a thinned first coat of Armstead Trade Floor Paint (up to 1 part white spirit to 10 parts paint). The normal finishing process is 1 or 2 full coats of Armstead Trade Floor Paint. Touch dry: 4-6 hours. Recoat: 16-24 hours. It is essential to allow the coated floor to dry for a minimum of 24 hours under well-ventilated conditions before use. Coverage up to 16m²/l on smooth surfaces of average porosity.